

Specifications		UTC-250 TM	UTC-250 T	UTC-280 T
Max. swing on std. center	mm	250	250	280
Swing with raising blocks	mm	350	350	380
Length between work head				
And RH tail stock	mm	330	520	610
Admit between centers	mm	440	670	760
Max. height center of wheel				
Above table	mm	300	300	380
Table :				
Longitudinal traverse	mm	400	480	510
Cross traverse	mm	200	250	250
Swivel either side of center				
(End scale)	deg.	-	9	9
Swivel LH/RH of column				
(Center scale)	deg.	45 ⁰ /45 ⁰	45 ⁰ /45 ⁰	45 ⁰ /45 ⁰
Size of table	mm	750x115	920x140	1010x140
Wheel Head :				
Vertical adjustment of wheel head	mm	210	210	290
Swivel	deg.	360 ⁰	360 ⁰	360 ⁰
Tilting in either direction	deg.	180 ⁰ ±	180 ⁰ ±	180 ⁰ ±
Spindle speed	rpm	3800/5600	3800/5600	3800/5600
Motor power	KW/HP	0.75/1	0.75/1	0.75/1
Shipping Dimensions				
Net weight of the machine	kg.	750	1150	1250
Gross weight of the machine	kg.	900	1350	1450
Overall size of machine				
L x W x H	mm	1075 x 1100 x 1400	1325 x 1170 x 1460	1325 x 1170 x 1460
Overall size of packing case				
L x W x H	mm	1200 x 1280 x 1550	1450 x 1350 x 1600	1450 x 1350 x 1600
Illustrations & specifications are not binding in detail & are subject to modification & improvement without notice.				